


LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
1K	2	B	ECR-13-001947	05MAR2013	LD JS

FINISHED CABLE DATA		
CONDUCTORS	WIRE AWG	23 AWG Solid
	Ø RANGE in mm)	0,546<=Ø<0,610
	MATERIAL	COPPER
	PLATING	BARE
INSULATION	ELONGATION	15% PER EN 50288-1
	MATERIAL	POLYETHYLENE
	OVERALL DIAMETER	1,40
DRAIN WIRE	WIRE AWG	-
	MATERIAL	-
	PLATING	-
	ELONGATION	-
BINDER	POLYESTER TAPE	OPTIONAL
INDIVIDUAL PAIR SCREEN	MATERIAL	PLASTIC LAMINATED ALUMINUM FOIL
OVERALL SHIELD	FOIL MATERIAL	-
OVERALL SHIELD	BRAID MATERIAL	COPPER BRAID
	PLATING	TINNED
	COVERAGE	40% APPROX.
	ELONGATION	15% PER EN 50288-1
JACKET	MATERIAL	LSFRZH
	OVERALL DIAMETER (D)	7,5 mm
PULLING FORCE	MAX.	110 N

- REFER TO PRODUCT SPEC 108-93018 FOR ADDITIONAL REQUIREMENTS.
- BASENR SPECIFIC PRINT LEGEND INFO:
CAT7A S/FTP XG SOLID PR04 AWG23 LSFRZH
- CABLE COLORED TYPES UPON REQUEST.



WHITE	1000	REEL	1711910-1
COLOUR	LENGTH (METRES)	PACKAGE	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	05Mar2013
DIMENSIONS: mm		CHK	05Mar2013
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	05Mar2013
0 PLC	±-	PRODUCT SPEC	
1 PLC	±-	APPLICATION SPEC	
2 PLC	±-	WEIGHT	
3 PLC	±-	CUSTOMER DRAWING	
4 PLC	±-	SCALE NTS	
ANGLES	±-	SHEET 1 OF 1	
MATERIAL	FINISH	REV B	

STE TE Connectivity

NAME: CABLE, CAT7A, S/FTP, PIMF1000, XG, SOLID, PR04, AWG23, LSFRZH

SIZE: A3 CAGE CODE: - DRAWING NO: C-1711910 RESTRICTED TO: -