

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2013

© COPYRIGHT 2009

TE CONNECTIVITY AMP ESPAÑA S.L.U.

ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
1K	2	B	ECR-13-000227	15JAN2013	RM JS

SCALE 2:1

1. PACKAGING: ONE JACK IN A BLISTER BOX (INCLUDING INSTRUCTION SHEET 411-93013). TEN BLISTER BOX IN A CARTON BOX (INCLUDING TWO TOOL SUPPLEMENT). 200 JACKS IN A SHIPPING BOX ACCORDING.

2. ITEMS SHIPPED NOT ASSEMBLED.

3. PACKAGING:  
 PRIMARY PACKAGING: PVC TRAY INCLUDING 12 JACKS.  
 TWO PVC TRAYS IN A CARTON BOX WITH ONE INSTRUCTION SHEET 411-93013.  
 DASH 7--1: 24 JACKS (2 TRAYS + 1 INSTRUCTION SHEET PER BOX) WITH CORRESPONDING LABEL.  
 360 JACKS IN A SHIPPING BOX ACCORDING.

4. AMP-TWIST 7AS SL JACK WILL TERMINATE:  
 • SOLID CONDUCTORS: 22-24 AWG.  
 • MAX. INSULATION DIAMETER:  $\varnothing 1.60$  mm  
 • MAX. CABLE JACKET DIAMETER:  $\varnothing 9.00$  mm

SUGGESTED FLUSH MOUNT  
PANEL APPLICATION CUTOUT

SINGLE PANEL CUTOUT

SCALE 2:1

1	1	SUBASSY REAR HOUSING	2
1	1	SUBASSY FRONT HOUSING WITHOUT DUST COVER	1
7--1	3		
	1		
		DESCRIPTION	ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN R. MATEO 02AUG2007

CHK A. PUELL 02AUG2007

APVD J. SANABRA 06FEB2008

PRODUCT SPEC 108-93019

APPLICATION SPEC 411-93013

WEIGHT -

Customer Drawing

TE Connectivity

 NAME  
 AMP-TWIST 7AS SL JACK  
 WITHOUT DUST COVER

SIZE A3 CAGE CODE - DRAWING NO C-1711437 RESTRICTED TO -

SCALE 1:1 SHEET 1 OF 1 REV B

DIMENSIONS:  
mmTOLERANCES UNLESS  
OTHERWISE SPECIFIED:


 0 PLC  $\pm 0.15$   
 1 PLC  $\pm 0.25$   
 2 PLC  $\pm 0.30$   
 3 PLC  $\pm 0.40$   
 4 PLC  $\pm 0.50$   
 ANGLES  $\pm 0.5$ 

MATERIAL -

FINISH -

1470-19 (3/11)