

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2013

© COPYRIGHT 2009

TE CONNECTIVITY AMP ESPAÑA S.L.U.

ALL RIGHTS RESERVED.

| LOC | DIST | REVISIONS | | | | |
|-----|------|-------------|---------------|-----------|------|----|
| P | LTR | DESCRIPTION | DATE | DWN | APVD | |
| 1K | 2 | B | ECR-13-000227 | 15JAN2013 | RM | JS |
| | | | | | | |
| | | | | | | |

SCALE 2:1

1. PACKAGING: ONE JACK IN A BLISTER BOX (INCLUDING INSTRUCTION SHEET 411-93013). TEN BLISTER BOX IN A CARTON BOX (INCLUDING TWO TOOL SUPPLEMENT). 200 JACKS IN A SHIPPING BOX ACCORDING.

2. ITEMS SHIPPED NOT ASSEMBLED.

3. PACKAGING:
 PRIMARY PACKAGING: PVC TRAY INCLUDING 12 JACKS.
 TWO PVC TRAYS IN A CARTON BOX WITH ONE INSTRUCTION SHEET 411-93013.
 DASH 7--1: 24 JACKS (2 TRAYS + 1 INSTRUCTION SHEET PER BOX) WITH CORRESPONDING LABEL.
 360 JACKS IN A SHIPPING BOX ACCORDING.

4. AMP-TWIST 7AS SL JACK WILL TERMINATE:
 • SOLID CONDUCTORS: 22-24 AWG.
 • MAX. INSULATION DIAMETER: $\varnothing 1.60$ mm
 • MAX. CABLE JACKET DIAMETER: $\varnothing 9.00$ mm

SUGGESTED FLUSH MOUNT
PANEL APPLICATION CUTOUT

SINGLE PANEL CUTOUT

SCALE 2:1

| | | | |
|------|---|--|------|
| 1 | 1 | SUBASSY REAR HOUSING | 2 |
| 1 | 1 | SUBASSY FRONT HOUSING WITHOUT DUST COVER | 1 |
| 7--1 | 3 | | |
| | 1 | | |
| | | DESCRIPTION | ITEM |

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN R. MATEO 02AUG2007

CHK A. PUELL 02AUG2007

APVD J. SANABRA 06FEB2008

PRODUCT SPEC 108-93019

APPLICATION SPEC 411-93013

WEIGHT -

Customer Drawing

TE Connectivity

NAME
AMP-TWIST 7AS SL JACK
WITHOUT DUST COVER

SIZE A3 CAGE CODE - DRAWING NO C-1711437 RESTRICTED TO -

SCALE 1:1 SHEET 1 OF 1 REV B

DIMENSIONS:
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:

| | |
|--------|----|
| 0 PLC | ±- |
| 1 PLC | ±- |
| 2 PLC | ±- |
| 3 PLC | ±- |
| 4 PLC | ±- |
| ANGLES | ±- |

MATERIAL -

FINISH -

1470-19 (3/11)