

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2013

© COPYRIGHT 2009

TE CONNECTIVITY AMP ESPAÑA S.L.U.

ALL RIGHTS RESERVED.

LOC	DIST
1K	2

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D	ADDED CABLE TERMINATION RANGE (NOTE 3)	05MAR2009	RM	JS

1. ITEMS SHIPPED NOT ASSEMBLED.

2. PACKAGING:
 DASH -1: EACH JACK IN A BLISTER BOX INCLUDING A INSTRUCTION SHEET 411-93013
 10 BLISTER BOXES IN A CARTON BOX (INCLUDING TWO TOOL SUPPLEMENTS).
 200 JACKS IN A SHIPPING BOX.
 DASH 7- -1: 24 JACKS (2 TRAYS + 1 INSTRUCTION SHEET PER BOX)
 PVC TRAY INCLUDING 12 JACKS. TWO PVC TRAYS IN A CARTON BOX
 WITH ONE INSTRUCTION SHEET 411-93013.
 360 JACKS IN A SHIPPING BOX.

3. AMP-TWIST 7AS SL JACK WILL TERMINATE:
 • SOLID CONDUCTORS: 22-24 AWG.
 • MAX. INSULATION DIAMETER: $\varnothing 1.60$ mm
 • MAX. CABLE JACKET: $\varnothing 9.00$ mm

SCALE 2:1

14.78

7.92

14.78

20.32

17.20

20.25

1.47 - 1.60

PANEL THICKNESS

SUGGESTED FLUSH MOUNT
PANEL APPLICATION CUTOUT

SINGLE PANEL CUTOUT

23.45 REF

20.62 REF

3.54 REF

23.45 REF

33.10 REF

36.50 REF

26.34 REF

14.48 REF

1	1	SUBASSY REAR HOUSING	2
1	1	SUBASSY FRONT HOUSING WITH DUST COVER	1
7--1	-1	DESCRIPTION	ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN R. MATEO 02MAY2007

CHK A. PUELL 07MAY2007

APVD J. SANABRA 13DEC2007

PRODUCT SPEC

108-93019

APPLICATION SPEC

411-93013

WEIGHT -

Customer Drawing

TE Connectivity

NAME		AMP-TWIST 7AS SL JACK WITH DUST COVER	
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	-	C-1711441	-

SCALE	SHEET	OF	REV
1:1	1	1	D

DIMENSIONS:

mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

FINISH -

MATERIAL -

SCALE 2:1

1470-19 (3/11)