

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2015

© COPYRIGHT 2015 TE CONNECTIVITY AMP ESPAÑA S.L.U. ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D	ECR-15-002896	26FEB2015	RM	JS

1. RJ45 CATEGORY 5E PATCH CABLE ASSEMBLIES ARE USED AS PATCH LEADS IN GENERIC CUSTOMER PREMISES CABLING ACCORDING TO ISO/IEC 11801. THEY CAN ALSO BE USED AS WORKSTATION/EQUIPMENT LEADS TO MAINTAIN CHANNEL PERFORMANCE.

2. EACH ASSEMBLY IS SUPPLIED IN A CLEAR BAG.

3. FOR AVAILABLE DASH LENGTHS, DIM "A" SEE TE CONNECTIVITY CATALOG.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

MATERIAL

-

FINISH

-

DWN J. GATNAU 30JAN2007

CHK M. MAQUEDA 30JAN2007

APVD J. SANABRA 30JAN2007

PRODUCT SPEC
108-93009

APPLICATION SPEC

WEIGHT

-

NAME			
RJ45 PATCH CABLE ASSEMBLY PCat5E, F/UTP, LSZH, STRD, BLUE			

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	-	©-959308	-

Customer Drawing

SCALE

SHEET

1

OF

1

REV

D

1470-19 (3/13)